

## Features

- **LiFePO<sub>4</sub> performance in highly applicable sizes**
  - Designed for seamless replacement of existing 12V 100Ah lead acid batteries in most applications.
- **Ultra-efficient recharge capability**
  - Absorbs >96% of total charge energy supplied (max. 4% lost) every time, even at C1 rates.
  - Resilient against erratic charge & immune to associated lead acid vulnerabilities such as sulfation-induced capacity degradation.
- **Compatible with more than just 12V systems**
  - Up to 4 x batteries can be connected in series for installation in compatible 48V systems.
- **3 year product warranty.**

incl.  **Bluetooth™**  
monitoring



## Technical Specifications

### GENERAL SPECIFICATIONS

Battery chemistry	Lithium Iron Phosphate (LiFePO <sub>4</sub> )
Nominal voltage	13VDC
Usable capacity	1404Wh @C10, 25°C
Operating voltage range	11.6V ~ 14.2V
Operating temperature range	Charge: 0°C ~ 45°C   Discharge: -20°C ~ 65°C
Cycle life @100% DoD, C10, 25°C	> 2000 cycles (1404Wh)
Cycle life @80% DoD, C10, 25°C	> 3000 cycles (1123Wh)
Cycle life @50% DoD, C10, 25°C	> 5000 cycles (702Wh)
Dimensions	330 x 175 x 195mm (W x D x H)
Net weight (unboxed)	12.5kg
Warranty period	3 years
Terminal size & type	M8 (female)

### VOLTAGE & CURRENT

Bulk voltage (max. operating voltage)	14.2V
Float voltage (continuous charge voltage)	13.9V
Low voltage (min. operating voltage)	11.6V
Charge current	Recommended: 50A (C2)   Maximum: 100A
Discharge current	Recommended: 50A (C2)   Maximum: 100A   Peak: 350A (for <5 seconds)
Self-discharge rate	< 3% per month
Charge & discharge efficiency	96 ~ 99% @C1

### SAFETY FEATURES

Ingress protection rating	IP54
Current over-charge protection range	Charge: 105A   Discharge: 350A
Voltage over-charge protection	< 14.8V (auto cut-off at first V <sub>cell</sub> ≥ 3.7V)
Voltage over-discharge protection	> 10V (auto cut-off at first V <sub>cell</sub> ≤ 2.5V)