


Datasheet of 20W LED Prime Series Floodlight

Product Name 20W LED Prime Series Floodlight
 Product SKU ML-PRM-20W-6K

Product Characteristics

- 100 Lumens per watt
- Equipped with a massive 3kV Surge Protection
- Wide input voltage AC170-264V
- Design allows for autoproduction which provides a truly stable, reliable and cost effective solution to the floodlight market
- Robust ADC12 graded die-cast aluminium housing
- H05RN, 3*1.0mm², 0.5m
- IP65 / IK08
- 2 year warranty



Application Residential, Domestic, Industrial

Product Specification

Power	20W
LEDs	 国星光电 SMD2835
Lumen	2000 lm
Colour	6500K
Colour Rendering Index	RA>80
UGR Rating	<27
Beam Angle	110°
Operating Temperature	-20°C~+45°C
Lifespan	30,000hrs@25°C, L70B50
Driver	Multi-Segment Linear DOB
Power Factor	0.9PF
Input Voltage	AC170-264V
Input Frequency	50/60Hz
Dimmable	Non-dimmable
Surge Protection	3kV
IK Rating	IK08
Energy efficiency class	Class F
Ingress Protection Rating	IP65
Cable	Rubble, H05RN, 3*1.0mm ² , 0.5m
Main Materials	ADC12 Graded Aluminium
Certifications	IEC / CB / CE / ROHS
Warranty	2 Year Warranty
Dimensions	120mm(L) * 100mm(W) * 22mm(H)



Comments..... Project.....