

Datasheet of 50W4030 CCT LED Trifecta Floodlight

Product Name 50W LED Trifecta Floodlight
 Product SKU ML-TFT-50W4030-CCT

- Product Characteristics
- Samsung LED chip
 - Built-in Driver with Switched IC
 - L/N-PE:2kV, L-N: 1kV Surge Protection
 - Wide input voltage AC110-277Vac
 - The new patented housing has an ADC12 graded-aluminum oblique bracket for extra strength
 - ADC12 die-cast aluminium galvanized steel bracket[SGCC]
 - IP65 / IK18
 - 5 year warranty



Application Commercial, Industrial, Residential Lighting

Product Specification

| | |
|---------------------------|---|
| Power | 50W/40W/30W |
| LEDs | SAMSUNG |
| Effective Lumen | 7000lm/5600lm/4200lm (All in one) |
| Colour | 6500K+4000K+3000K (All in one) |
| Colour Rendering Index | RA>80 |
| EMC | Passed |
| Beam Angle | 110° |
| Driver | Built-in Driver with Switched IC |
| Surge Protection | L/N-PE: 2kV, L-N: 1kV |
| Power Factor | 0,9PF |
| Input Voltage | AC110-277V |
| Input Frequency | 50/60HZ |
| Operating Temperature | -40°C - 50°C |
| Dimmable | No |
| Lifespan | 50,000 hours |
| Warranty | 5 Years |
| Ingress Protection Rating | IP65 |
| Cable | H05, 1M, 3*1mm |
| Main Materials | ACDC12 Aluminum Housing, Galvanized Steel Bracket[SGCC] |
| Certifications | IEC / CE / ROHS / ErP / REACH / SAA / IEC60598-1&2 |
| Dimension | (L)200mm * (W)150mm * (H)29.6mm |



Comments..... Project.....