

Product datasheet

Specifications



Miniature circuit-breaker. Acti9 iC60a. 2P. 63 A. C curve. 4500 A (IEC 60898-1). 6 kA (IEC 60947-2)

A9F64263

Price: 848,41 ZAR

Main

| | |
|---------------------------|---|
| Device application | Distribution |
| Range | Acti9 |
| Product name | Acti9 iC60 |
| Product or component type | Miniature circuit-breaker |
| Device short name | iC60a |
| poles description | 2P |
| Number of protected poles | 2 |
| [In] rated current | 63 A |
| network type | AC |
| Trip unit technology | Thermal-magnetic |
| Curve code | C |
| Breaking capacity | 4500 A Icn at 400 V AC 50/60 Hz conforming to EN/IEC 60898-1 10 kA Icu at 220...240 V AC 50/60 Hz conforming to EN/IEC 60947-2 6 kA Icu at 380...415 V AC 50/60 Hz conforming to EN/IEC 60947-2 |
| Utilisation category | Category A conforming to EN 60947-2 Category A conforming to IEC 60947-2 |
| Suitability for isolation | Yes conforming to EN 60898-1 Yes conforming to EN 60947-2 Yes conforming to IEC 60898-1 Yes conforming to IEC 60947-2 |
| Standards | IEC 60947-2 IEC 60898-1 EN 60947-2 EN 60898-1 |

Complementary

| | |
|--|---|
| network frequency | 50/60 Hz |
| Magnetic tripping limit | 8 x In +/- 20 % |
| [Ics] rated service breaking capacity | 10 kA 100 % conforming to EN 60947-2 - 220...240 V AC 50/60 Hz 6 kA 100 % conforming to EN 60947-2 - 380...415 V AC 50/60 Hz 10 kA 100 % conforming to IEC 60947-2 - 220...240 V AC 50/60 Hz 6 kA 100 % conforming to IEC 60947-2 - 380...415 V AC 50/60 Hz 4500 A 100 % conforming to EN 60898-1 - 400 V AC 50/60 Hz 4500 A 100 % conforming to IEC 60898-1 - 400 V AC 50/60 Hz |
| Limitation class | 3 conforming to EN 60898-1 |
| [Ui] rated insulation voltage | 500 V AC 50/60 Hz conforming to EN 60947-2 500 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to EN 60947-2 6 kV conforming to IEC 60947-2 |

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

| | |
|----------------------------|---|
| Contact position indicator | Yes |
| Control type | Toggle |
| local signalling | Trip indicator |
| mounting mode | Removable comb busbar installed |
| mounting support | DIN rail |
| 9 mm pitches | 4 |
| Width | 36 mm |
| Colour | White |
| Connections - terminals | Single terminal (top or bottom) 1...35 mm ² rigid Single terminal (top or bottom) 1...25 mm ² flexible |
| Wire stripping length | 14 mm for top or bottom connection |
| Tightening torque | 3.5 N.m top or bottom |
| Earth-leakage protection | Separate block |

Environment

| | |
|---------------------------------------|---|
| IP degree of protection | IP20 B conforming to EN/IEC 60529 |
| Pollution degree | 3 conforming to EN 60947-2 3 conforming to IEC 60947-2 |
| Overvoltage category | II |
| Tropicalisation | 2 conforming to EN/IEC 60068-2-78 |
| Relative humidity | 95 % |
| Operating altitude | 0...2000 m |
| Ambient air temperature for operation | -35...70 °C |
| Ambient air temperature for storage | -40...85 °C |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 7.300 cm |
| Package 1 Width | 3.500 cm |
| Package 1 Length | 9.400 cm |
| Package 1 Weight | 275.000 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 6 |
| Package 2 Height | 7.700 cm |
| Package 2 Width | 9.700 cm |
| Package 2 Length | 22.300 cm |
| Package 2 Weight | 1.652 kg |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 66 |
| Package 3 Height | 30.000 cm |
| Package 3 Width | 30.000 cm |

| | |
|------------------|-----------|
| Package 3 Length | 40.000 cm |
|------------------|-----------|

| | |
|------------------|-----------|
| Package 3 Weight | 18.172 kg |
|------------------|-----------|

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Halogen Free Product

Certifications & Standards

| | |
|--------------------------|---|
| Reach Regulation | REACH Declaration |
| Eu Rohs Directive | Compliant with Exemptions |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | No need of specific recycling operations |