

Product Name 150W LED Canopy light IP65 Product SKU ML-CMDS-150W-57K

Product Characteristics

Universal voltage AC100-305V 50/60HzUsing high quality 3030 chips, LM-80 report and IES data available

• High Power Factor >0.95, Low THD Driver.

•The whole lamp with the powder coating is brighter, without fading and corrosion.

 Flat grind arenaceous glass lens.
Built-in light module, easy maintenance, low maintenance costs.

•Built-in light module, easy maintenance, low maintenance costs.

•Dust-proof and waterproof, I P65.

•5 years Warranty.



Fuel Station Application

Product Specification	
Power	150W
LEDs	UMILEDS
Raw Lumen	22000 lm
Effective Lumen	20000 lm
UGR Rating	Unified Glare Rating < 20
Colour	5700K
Colour Rendering Index	RA>80
Beam Angle	120°
LED Chip Lifespan	L90 @ 50,000 hours / L80 @ 72,000 hours
Driver	MANUELL.
Power Factor	0,97PF
Input Voltage	AC100-305V
Input Frequency	50/60HZ
Dimmable	0-10V / PWM / Resistor Dimming
Surge Protection	10kV
Driver Lifespan	62,000 hours
Emergency Backup	Available
Ingress Protection Rating	IP65
Impact Rating	IK08
Operating Temperature	-30°C - 50°C
Main Materials	1070 Graded Aluminium / TGIC powder coating to prevent corrosion
Mounting Option	Recessed Outlet / Surface Mount Bracket Option Available
Dimension	365mm (L) * 365mm (W) * 70 mm (H)
Certifications	EMC / CE / ROHS / IEC
Warranty	5 Years

